				- 1		1
Λ	. /	؍ ا	\ \	\neg	$\overline{}$	-
	\ /	17	1/		\sim	
	V	1	\mathcal{N}	1		٠







	AP13	AL19	AL25		
Detector Specifications					
Туре	Uncooled Vox				
Resolution	256×192		384×288		
Pixel Size, µm	12				
NETD, mK	≤ 40				
Frame Rate, Hz	25)			
Optical Specifications					
Objective Lens, mm	13	19	25		
FOV	13.5°×10.1°	13.8°×10.4°	10.5°×7.9°		
Digital Zoom, x	1/2		/ 4		
Diopter, D	-3 ~ +1		-7 ~ +2		
Detection Range, m (Target Size: 1.7m×0.5m, P(n)=99%)	675	986	1298		
Display Specifications					
Туре	LC	OS	OLED		
Resolution	720×540		640×400		
Battery Power Supply					
Battery Type / Capacity / Output Voltage	Built-in lithium ion battery / 3.6Ah / 3.6V				
Working Hours (22°C), h*	9.5		5		
External Power Supply	5V (Type C)				
Physical Specifications					
Ingress Protection Rating	IP67				
Memory Capacity, GB	32				
Wi-Fi / APP	Support (InfiRay outdoor)				
Operating Temperature, °C	-10 ~ +50		-10 ~ +70		
Weight, g	<340	<350			
Dimensions, mm	160×60×60	169×60×60			



IRay Technology Co., Ltd.

Tel: 400-998-3088 Fax: +86-535-3410604
Mail: infirayoutdoor@infiray.com Web: www.infirayoutdoor.com
Add: 11th Guiyang Street, YEDA, Yantai 264006, P.R.China





Thermal Imaging Monocular

AFFO Series

The AFFO Series handheld thermal imager is an entry-level thermal imager for hunting users, featuring both a fashionable appearance and a more compact size. The AFFO Series uses a self-developed 12µm detector with 256×192/384×288 resolution to produce crisp images and supports photo taking and video recording with its built-in high-speed 32GB storage capacity.

AP13/AL19/AL25













AFFO AP13

- High-performance Detector

12_{µm}

The AFFO Series adopts 12 μ m 256×192/384×288 resolution uncooled Vox thermal imaging sensor, the self-developed high-performance sensor enables crisp HD images.

Red ring design

- Charactive Brand New Appearance Design

Rounded curve-design body fits human hand shape, making it more comfortable to hold.



design

HDMI interface to display HD videos on external devices

Designed with HDMI interface (high-definition multimedia interface) uses full digital signal transmission, which not only provides full digital video signal, but also transmits audio at the same time. This device can be directly connected to HD screens, laptops, etc. for high-quality display.



HDMI

Long Battery Life

Low power elements used in AFFO Series provide sufficient operation time. Up to 9.5 hours operational battery life.



- Additional Practical Functions

The AFFO Series features additional practical functions including stadiametric rangefinding and PIP.

Its adapter is equipped with multiple travel charging headers to meet the needs of use in different countries and regions.

1.Stadiametric Rangefinding:

Facilitate confirmation of prey distance and provide position reference for hunting



Stadiametric Rangefinding

2 DIE

The screen of cursor position is magnified twice to highlight the target and assist in observing the target details



PIP

More image modes to cope with different scenarios


Hot target highlight mode provides better object highlighting capability with more options of white hot, black hot, red-hot and color palette. Wider detection and operating temperature ranges with hotspot tracking function.



The 32GB memory of AFFO Series makes it possible to record all night, meeting the requirements of whole-hunting process recording.



32GB



1. Upgraded lens protection:

Durable rigid plastic lens cap with higher hardness and impact resistance;

2. Upgraded waterproofing:

External screen is used in rainy days for outdoor scenarios to prevent water flowing into the interface.

